
# Rent this machine today. Visit: sweeperland.com/Rental-Contact.html



From chip seal and milling operations to heavy spring clean-up, the Stewart-Amos Sweeper Co.'s Starfire S-4 can handle it.


The S-4 is a four wheel, dual engine, mechanical broom street sweeper that has a compact design, but is as productive as sweepers mounted on larger trucks.

Manufactured with reliability and simplicity in mind, the S-4 is built for day-in and day-out continuous duty sweeping. The short wheelbase chassis combines tight maneuverability like a 3-wheel sweeper, yet is still capable of traveling at highway speeds between job-sites.

### The benefits of the Starfire S-4 include:

- 4.0 Cubic Yard Hopper
- High Performance Sweeping
- Large Volume Dust Suppression
- Variable Height Dumping
- Great Maneuverability and Mobility
- Rugged Construction
- Extremely Fuel Efficient
- Front & Rear Canopy Enclosures Maximize Component Protection
- Three Shaft Elevator Design

- Ease of Maintenance
- Simplicity of Design
- Remarkably Quiet
- Safety Monitoring Camera System
  PM-10 Certified Rule 1186
- Quad (4) "X" Style Hopper Scissor Lift
- 4 Corner Hopper Lift
- Spring Balanced Brooms Auto Compensate for Wear
- Proudly made in the U.S.A



No CDL License Required




# **Exclusive 3-Shaft Elevator**

## **BENEFITS:**

**LONGER LASTING.** 3rd shaft ensures just the right amount of upper chain support and tension. Extends chains wear life and eliminates chain slapping.

**REDUCED MAINTENANCE COSTS.** 3rd shaft doubles amount of available chain adjustments. This and optimum upper chain support reduces chain wear and need to remove chain links by more than 50%.

**BETTER LOADING PERFORMANCE.** Maintains unrestricted debris movement. 3rd shaft maintains optimum chain spacing ensuring effective sweeping of large/bulky debris to minimize clogging.





Massive quad (4) "X" style lift scissors with four corner lift provide exceptional hopper stability especially when dumping wet, unbalanced or

# S-4 SPECIFICATION



Sweeping Path: 10' maximum

Sweeping Pam: 10 maximum
Debris Hopper: 4.0 cubic yards volumetric
Dump Height (variable): 16" to 122"
Turning Radius\*: 18' 6"
Overall Length\*: 22'
Overall Height\*: 102.5" including Strobe Lights
GVWR\*: 19,500#

Main Broom: Length: 58" Diameter: 36" Type: Chevron

Drive: Hydraulic motor/direct drive and reversible Mounting: Full floating, trailing arm, with shocks Lift Control: Hydraulic, in-cab

Speed: Variable with aux. engine rpm Dirt Shoes: Carbide, 2" wide

## **Dual Gutter Brooms:** Diameter: 42"

Diameter: 42
Type: Spring balanced, auto wear compensating
Drive: Hydraulic and reversible
Mounting: Free-floating, trailing arm
Lift Control: Hydraulic, in-cab

Tilt control; in-cab (electric) Speed: Variable with aux. engine rpm Dual Float Protected

**Ekevator System:**Type: 7-flight squeegee with replaceable rubber

edging Liner: Bolt-in, 2 piece AR steel plates Chain: HD constant radius roller chain Sprockets: Urethane

Shafts: Three (see side bar above) Drive: Hydraulic, in-cab, and reversible

Lift Control: Hydraulic, in-cab Elevator Jam Warning: Buzzer and light in-cab Flushing System: Built-in

Debris Hopper:

Volumetric Capacity: 4.0 cubic yards Dump Height (variable): 16" to 122" Hopper Door Reach from Side: 44" Inspection door, window, and safety props 4 Corner hopper lift Quad (4) "X" style lift scissors

Pump: Dual tandem gear Capacity: 22 gpm @ 2000 rpm Reservoir: 45 gallons Hydraulic Oil Filter: 10 micron

Oil Cooler: Electric remonte mounted Integral hydraulic pressure gauges

Water Spray System: Tank Capacity: 200 gallons Construction: Polyethylene Mounting: Removablé Pump: 3.6 GPM electric diaphragm

Spray Nozzles: • 4 on front spray bar

• 2 on each gutter broom

• 4 on main broom

Fill Hose: 20' with NST coupler with anti-siphon air gap Water Pump Prefilter: 80 mesh

**Electrical System:**Alternator: 120 AMP Voltage: 12 volt LED Lights: front and rear strobes; gutter brooms and rear mounted working lights; license plate; 2 stop/turn/tail; and clearance lights Backup alarm

**Camera and Monitor Safety System:** 

7" Color monitor with right side gutter broom and rear mounted color cameras

### **Instrumentation and Controls:**

Sweeper function rocker switches Elevator stall alarm and light Auxiliary engine hour meter and tachometer Electric throttle Console night light

Sweeper Engine: Make: Kubota V2403-M-T-E3 Tier 3 Compliant/T4 Interim Horsepower: 59 @ 2700 rpm Type: in-line, four-cylinder turbo diesel

Paint: Body: Standard white high-gloss urethane enamel Undercarriage: Flat black enamel

Auto pickup in reverse Auto shutdown for high temperature/low pressure Independent left and right gutter broom operation 30 gallon, common fuel tank Operators, parts and maintenance manuals

**Limited Warranty Policy:** 

The Starfire S-4 sweeper is guaranteed to be free from defects due to faulty materials and/or workmanship for a period of 12 months, or 1,000 hours (whichever occurs first). Liability is limited to replacement of defect parts at factory or authorized dealer. The standard warranty of the chassis manufacturer and auxiliary engine applies.

Available Options: (not included in base price)

Arrow Board Strobe/Beacon protector Front mounted magnet Brush style dirt shoes
100 gallon auxiliary water tank
Dual 3.6 GPM Water pumps for 7.2 GPM **Epoxy Hopper liner** Stainless steel hopper Extended warranties Body paint colors Auto Lube System Hopper Vibrator On-Board Hi-Pressure Wash down System (w/ 50' hose and wand)
Others upon request
Wide variety of available chassis\*\* \*\*Consult your dealer for details

Please read actual warranty for details and limitations





Rent this machine today. Visit: sweeperland.com/Rental-Contact.html

