

## ADSPRAY™ 1000XPC/D

### P R E S S U R E   W A S H E R S

The *AdSpray* pressure washers blast away dirt and grime for fast and efficient cleaning. Fast because they power clean... efficient because the chemical reaches areas you can't. Chemical is sprayed on with low pressure, then dirt is blasted off with high-pressure power.

The *AdSpray 1000XPC* and *1000XPCD* are cart-mounted models with adjustable pressure to 1000 p.s.i. (69 bar) for various applications.

The spray gun has trigger on/off spray control, and is at the end of a 40 foot (12 m) long hose. Nozzle tip turns to vary the spray pattern from zero to sixty degrees. A high/low pressure nozzle control switches between low pressure chemical application (to save on costly chemicals) and high pressure rinse.

The *AdSpray 1000XPC* with its 1.5 horsepower, 115 volt motor provides ample power to a 2.2 g.p.m. (8.3 l./min.) pump. An inlet water filter traps contaminants to protect pump from premature wear, and chemicals are injected at variable rates, "after the pump" for additional protection. This machine handles water up to 140° F (60° C). Ceramic plunger, forged crankshaft, stainless steel valves and other features assure durable pump performance. In fact, the pump has a five-year warranty.

The *AdSpray 1000XPCD* has a 1.5 hp, 115 volt motor which provides ample power to a 2.2 g.p.m. (8.3 l./min.) pump. An electrical thermal valve with on/off indicator light, protects the pump by shutting the unit off if it is left on by mistake. The pump can handle water up to 180° F (82° C), and has a one-year warranty.

Cord and hose storage is built into the roto-molded high-density polypropylene handle. This unique handle/frame design is also a six gallon (22 l.) cleaning solution tank.

The *AdSpray 1000XPC* and *1000XPCD* offer cleaning power, portability and economy, with a variety of accessories to meet your cleaning needs.



#### Comes With:

- Hose
- Wand
- Heavy-duty ground-fault circuit breaker protection
- Inlet water filter protection for pump
- High/low down-stream chemical injection

To maintain the peak performance of your floor maintenance equipment, buy only genuine **apa** parts and accessories.

# S P E C I F I C A T I O N S



The *AdSpray 1000XPC* has a rugged pump with ceramic pistons and aluminum cylinder head helps to maintain high performance. The mechanical thermal valve protects the pump if wand is left on in error. Pump has five-year warranty.

The high-performance pump for the *AdSpray 1000XPCD* has ceramic pistons with brass cylinder. Electric thermal valve protects the pump by shutting the unit off if it is left on accidentally. The pump can handle water up to 180° F (82° C), and has a one-year warranty.



Chemicals are injected after the pump, so they can't cause problems to valves or seals. Ratios are set and locked in with controls by the operator. Chemical metering saves cost by reducing waste.



The rotomolded polypropylene handle/frame is specially designed to also be a built-in six gallon (22 l.) chemical tank. Its design also incorporates cord storage features for a neat package.

<b>Motor/Engine:</b>	1.5 horsepower, 115 volt/15 amp/60 Hz
<b>Power Cord:</b>	35' (10 m) long, w/ground fault interrupter
<b>Pump:</b>	Teflon graphite seals, ceramic coated steel pistons, stainless steel valves, ceramic plunger, and by-pass running against closed gun. The pump on the 1000XPC model is built to handle 140° F (60° C) water temperatures, and has a 5-year warranty. The pump on the 1000XPCD is built to handle 180° F (82°C) temperatures, and has a 1-year warranty.
<b>Output:</b>	Adjustable, to 1000 p.s.i. (69 bar), at - 2.2 g.p.m. (8.3 l./min)
<b>Chemical Injection:</b>	Variable rate, after the pump
<b>Gun:</b>	Two-piece 36" (91 cm) w/0-60° adjustable spray nozzle with high/low pressure switch, trigger on/off spray control and plastic insulation
<b>Hose:</b>	40' (12 m), non-marking, high-pressure
<b>Construction:</b>	ABS plastic motor/pump housing, frame and handle of high-density rotational molded polyethylene.
<b>Dimensions:</b>	Height — 45" (114 cm) Width — 15" (38 cm) Length — 25" (64 cm)
<b>Net Weight:</b>	Model 1000XPC – 105 lbs. (48 kg) Model 1000XPCD – 115 lbs. (52 kg)
<b>Shipping Weight:</b>	Model 1000XPC – 110 lbs. (50 kg) Model 1000XPCD – 120 lbs. (54 kg)

All specifications subject to change without notice.

## Product Part Number:

Model *1000XPC* – 100 113  
Model *1000XPCD* – 100 383



Nilfisk-Advance, Inc.  
14600 21st Avenue North  
Plymouth, MN, 55447-3408  
www.nilfisk-advance.com  
Phone: 800-989-2235  
Fax: 800-989-6566

Nilfisk-Advance Canada Company  
396 Watline Avenue  
Mississauga, Ontario, Canada, L4Z 1X2  
www.nilfisk-advance.com  
Phone: 800-668-8400 or 905-712-3260  
Fax: 800-263-5111 or 905-712-3255