

# Advance AdSpray™ 1500A Pressure Washer



(Shown with optional transport cart.)

#### Comes With:

- Hose
- Wand
- Heavy-duty ground-fault circuit breaker protection
- Inlet water filter protection for pump
- High/low down-stream chemical injection
- Mechanical thermal valve

The *AdSpray* pressure washers blast away dirt and grime for fast and efficient cleaning. Fast because they power clean... efficient because the chemical reaches areas you can't. Chemical is sprayed on with low pressure, then dirt is blasted off with high-pressure power.

The *AdSpray 1500A* is a hand-carried model with adjustable pressure to 1500 p.s.i. (103 bar) for various applications.

The spray gun has trigger on/off spray control, and is at the end of a 26 foot (8 m) long hose. Nozzle tip turns to vary the spray pattern from zero to sixty degrees.

A two horsepower, 115 volt motor provides ample power to a 2.1 g.p.m. (8 l./min.) pump. The pump has mechanical thermo-valve protection. An inlet water

filter traps contaminants to protect pump from premature wear, and chemicals are injected at variable rates, "after the pump" for additional protection. Ceramic coated pistons, ceramic plunger, teflon graphite seals and other features assure durable pump performance. In fact, the pump has a five-year warranty.

The *AdSpray 1500A* offers cleaning power, portability and economy, with a variety of accessories to meet your cleaning needs.



**Advance**  
by Nilfisk-Advance

# Advance AdSpray™ 1500A Pressure Washer



Chemicals are injected after the pump, so they can't cause problems to valves or seals. Ratios are set and locked in with controls by the operator. Chemical metering saves cost by reducing waste.



The optional Turbo Wand attachment creates a circular movement to the high-pressure spray. The effect can increase the cleaning impact of the pressure washer by as much as 85%.



The compact 1500A is packaged small with a built-in handle, so it's easy to hand-carry from one job site to another. Transport cart (shown on reverse) is optional.

**PUMP HAS  
5-YEAR  
WARRANTY**



The AdSpray 1500A has a dependable plunger-type pump and mechanical thermal relief valve, for a long life with few repairs, and greater cleaning productivity even with extended periods of use.

## Setting Standards...

- Our products are value-priced to give you the best combination of price and performance for your investment.
- You can get expert service and maintenance for your products by factory-trained personnel around the world, as well as fast parts delivery.
- Maintain peak performance with genuine **apa** parts.

## Technical Specifications

<b>Motor/Engine:</b>	Two horsepower, 115 volt/60 Hz	<b>Chemical Injection:</b>	Variable rate, after the pump
<b>Power Cord:</b>	6' (2 m) long, w/ground fault interrupter	<b>Gun:</b>	Two-piece 36" (91 cm) w/0-60° adjustable spray nozzle, trigger on/off spray control and plastic insulation
<b>Pump:</b>	Teflon graphite seals, ceramic coated steel pistons, stainless steel valves, aluminum head, mechanical thermal relief valve, ceramic plunger, and by-pass running against closed gun.	<b>Hose:</b>	26' (8 m),
<b>Output:</b>	Adjustable, to 1500 p.s.i. (103 bar), at - 2.1 g.p.m. (8 l./min)	<b>Dimensions:</b>	Height — 9" (23 cm) Width — 9" (23 cm) Length — 15.5" (39 cm)
		<b>Net Weight:</b>	50 lbs. (22.7 kg)
		<b>Shipping Weight:</b>	57 lbs. (26 kg)
		<b>Part Number:</b>	56 100 386 1500A 56 100 726 Optional Cart

Specifications are subject to change without notice.



Nilfisk-Advance, Inc.  
14600 21st Avenue North  
Plymouth, MN, 55447-3408  
www.nilfisk-advance.com  
Phone: 800-989-2235  
Fax: 800-989-6566

Nilfisk-Advance Canada Company  
396 Watline Avenue  
Mississauga, Ontario, Canada, L4Z 1X2  
www.nilfisk-advance.com  
Phone: 800-668-8400 or 905-712-3260  
Fax: 800-263-5111 or 905-712-3255

©1999, Nilfisk-Advance, Inc., Form L0771A, 8/99 Printed in U.S.A.