

ADVANCE

ADSPRAY™ 1500BGC ADSPRAY™ 1800HGC ADSPRAY™ 2000VGC

P R E S S U R E W A S H E R S

When you need hard-hitting impact for the toughest cleaning jobs, these gas engine-powered pressure washers are the answer. You can operate even at remote construction sites, far from electrical power sources.

Their integral transport cart frame construction and big wheels makes them extremely portable. And the handle-mounted chemical tank brings along 2 ½ gallons (9.5 liters) of cleaning solution.

The pumps on these three models generate up to 1500, 1800 or 2000 p.s.i. (103.4, 124, or 138 bar) with respect to the model number, but all have adjustable pressure. They can handle up to 140° F (60° C) inlet water temperature, with mechanical thermal relief valve protection. Chemicals are introduced to the system after the pump, so there's no chance of damage to the pump's working parts. Ceramic plungers, stainless steel valves, inlet water filter, oil bath bearing lubrication and many other features assure durability even with long, hard use. The pump for the 2000VGC has a one-year warranty, the pumps for the 1500BGC and 1800HGC each have a five-year warranty.

At the end of a 40 foot (12 m) pressure hose, the spray gun controls all operating functions so you don't have to keep returning to the unit. The grip has spray on/off control trigger. Its multi-reg nozzle controls the spray angle from 0-60°, as well as switching from high to low pressure for soap application. Both grip and wand are plastic insulated.

As with all Advance brand pressure washers, the wand accepts a variety of accessories for diverse cleaning needs.



Comes With:

- 40' (12 m) Hose
- Wand with Multi-Reg Tip

To maintain the peak performance of your floor maintenance equipment, buy only genuine **apa** parts and accessories.

S P E C I F I C A T I O N S



The AdSpray 1500BGC, 1800HGC and 2000VGC models have a dependable plunger-type pump with mechanical thermal relief valve, for a long life with few repairs, and greater cleaning productivity even with extended periods of use.



The chemical tank is handle-mounted, and holds 2 ½ gallons (9.5 l.) of cleaning solution. It's made of rust-proof, corrosion-resistant plastic that will not crack or peel. Convenient access opening makes it easy to fill.



These machines are ideal for outdoor use at remote locations where electric power is not readily available. Large 10" x 4" (25 x 10 cm) wheels on rugged, tubular steel cart frame make them easy to transport.



The spray gun has on/off spray control with insulated handle and two-piece insulated wand. The Multi-Reg spray nozzle adjusts from 0-60°, with high/low pressure adjustment for soap application. Variable spray pressure is adjustable at the pump.

	1500BGC	1800HGC	2000VGC
Engine (gasoline):	5 hp Briggs	5.5 hp Honda	9.5 hp Vanguard
Fuel Tank:	3 quarts	3.88 quarts	5 quarts
Pump:	Pump features on all three models include: teflon graphite seals, ceramic-coated steel pistons, stainless steel valves, aluminum pump head, mechanical thermal relief valve, ceramic plunger and by-pass running against closed gun.		
Output (adjustable):	1500 p.s.i. (103,4 bar) 3.5 g.p.m. (13 l./min.)	1800 p.s.i. (124 bar) 3.5 g.p.m. (13 l./min.)	2000 p.s.i. (138 bar) 4.5 g.p.m. (17 l./min.)
Chemical Tank:	2 ½ gallon (9.5 liters)		
Chemical Injection:	Variable rate, after the pump, on all models		
Gun/Wand:	Plastic insulated two-piece, 36" (91 cm) long wand with 0-60° adjustable spray nozzle, trigger on/off grip, high/low pressure switching multi-reg tip, for all models.		
Pressure Hose:	40' (12 m) long, non-marking, with quick-disconnect fittings for all models.		
Construction:	Strong, lightweight, tubular steel frame with large transport wheels for all models		
Dimensions:	27 ½" (70 cm) high 20" (51 cm) wide 26" (66 cm) long	27 ½" (70 cm) high 20" (51 cm) wide 26" (66 cm) long	29 ½" (75 cm) high 23" (58 cm) wide 30" (76 cm) long
Weights:	90 lbs. (41 kg) net 95 lbs. (43 kg) shpg.	90 lbs. (41 kg) net 95 lbs. (43 kg) shpg.	155 lbs. (70 kg) net 160 lbs. (73 kg) shpg.

All specifications subject to change without notice.

Product Part Number:

AdSpray 1500BGC — 100 121

AdSpray 1800HGC — 100 708

AdSpray 2000VGC — 100 125



Nilfisk-Advance, Inc.
14600 21st Avenue North
Plymouth, MN, 55447-3408
www.nilfisk-advance.com
Phone: 800-989-2235
Fax: 800-989-6566

Nilfisk-Advance Canada Company
396 Watline Avenue
Mississauga, Ontario, Canada, L4Z 1X2
www.nilfisk-advance.com
Phone: 800-668-8400 or 905-712-3260
Fax: 800-263-5111 or 905-712-3255