

Call toll free 1-800-626-7835

bortekindustries.com

Factory Cat equipment has a reputation for durability and unmatched cleaning performance. The new **MINIMAG** combines our proven cleaning ability with improved agility and operator productivity.

Factory Cats thrive in metal fabrication facilities, car dealerships, machine shops, food / beverage packaging and distribution, or in any application where customers demand much of their investments.

The **MINIMAG** is available with a large battery package and 17-gallon tanks, which reduce costly down time. There are multiple scrub paths available to better match your needs, in both disk and cylindrical styles.

The "Disk" machines offer nearly 35% more power than other machines. The deck is protected by steel guards and large polyurethane rollers keep the unit from marking walls. Brushes are driven by powerful motors, and are gimbal-mounted, to improve cleaning on uneven floors.

The "Cylindrical" machines have the added benefit of sweeping up debris while scrubbing. This may eliminate the need to presweep an area, increasing productivity.


Brush pressure is automatically maintained at one of five settings, on traction units, while the LCD provides diagnostics and hour meters, covering "transport", "scrubbing", "vacuum" and "key-on". The LCD also gives the operator a real-time view of systems running, battery level and scrubbing pressure. If the batteries become discharged, the unit automatically shuts down systems to allow it to return to the charge station.

The heavy steel construction, oversized motors, extra thick polyurethane tanks and stainless steel fasteners provide a solid foundation. The **MINIMAG** has a powerful, sealed transaxle for climbing steep ramps and the four point stance allow it to remain stable over rough terrain.

While offering the toughness you are looking for, your operators will find the *MINIMAG* easy to maneuver into tight areas, and simple to service.

EASY TANK CLEAN UP









SOLUTION GAUGE




REMOVABLE DEBRIS BASKET



TANK TIPS FOR ACCESS





RETURN ON INVESTMENT

AREA		TIME REQUIRED TO CLEAN		
Sq.	Ву	Model	Weekly	
Ft.	Hand	MINIMAG 26"	Savings	
10,000	7 hrs	0.5 hrs	\$ 220.00	
25,000	17 hrs	1.0 hrs	\$ 550.00	
75,000	50 hrs	3.0 hrs	\$1,650.00	
100,000	70 hrs	4.0 hrs	\$2,200.00	

EXPERIENCED DISTRIBUTORS

FACTORY CAT continues to grow by providing the toughest machines in our industry. Our 350 distributors in 36 countries each maintain a factorytrained service department and diverse rental fleet, which allow them to continue serving your needs.

We offer a line of cleaning equipment that includes sweepers and scrubbers in both walk-behind and rider models. All FACTORY CAT machines are practical, rugged and priced sensibly.

GUARANTEED SERVICE

We guarantee to supply you the spare parts you need within three workdays, or they are yours free. This applies only to the 48 contiguous states, at the customer's special request, and to parts that can be shipped by courier.



Your Facility Solutions Resource

bortekindustries.com

Call toll free 1-800-626-7835

Specifications	MINI 17" – 23" (Brush)	MINIMAG 17" – 28" (Traction)		
Body/Dimensions Tank Material: Chassis Construction: Front Wheels: Rear Casters: Size (L x W x H): Weight (w/batteries):	Poly (3/8" thick) 3/16" Coated Steel (2) 9" x 2" (2) 4" x 2" 45" x 18" x 40" 374 pounds	Poly (3/8" thick) 3/16" Coated Steel (2) 9" x 3" (2) 4" x 2" 45" x 18" x 40" 387 pounds		
Brush System Disk Brush/Pad Size:	17-FB: (1) 17" 20-FB: (1) 20" 23-FB: (1) 23"	17-FD: (1) 17" 20-FD: (1) 20" 23-FD: (1) 23" 26-FD: (2) 13" 28-FD: (2) 14"		
Disk Brush Motors (Standard): Disk Brush Motor (Optional): Cylindrical Brush Size: Cylindrical Brush Motor: Brush Down Pressure:	(1) 0.75 hp/200 rpm (1) 1.0 hp/200 rpm 0-125 pounds	(1) 0.75 hp/200 rpm (1) 1.0 hp/200 rpm 24-FC: (2) 22" (2) 0.75 hp/350 rpm 0-150 pounds		
Battery System System Voltage: Standard Battery Rating: Optional Battery Rating: Battery Run Time: Charger (110v/60 Hz/24 volt):	24 volts 115 ah 155 ah Up to 3.5 hours Automatic	24 volts 155 ah 225 ah Up to 3.5 hours Automatic		
Drive System Standard Drive: Forward Speed: Reverse Speed:	Brush Assist 0-230 ft/min (4 mph) 0-130 ft/min (2 mph)	0.5 hp all gear/sealed 0-230 ft/min (4 mph) 0-130 ft/min (2 mph)		
Solution System Solution Tank Capacity: Solution Flow Rate: Solution Filter:	17 gallons 0 - 1.0 gpm Stainless/Inline	17 gallons 0 - 1.0 gpm Stainless/Inline		
Recovery System Recovery Tank Capacity: Vacuum Power: Drain Hose: Vacuum Specs (lift/airflow): Demisting Chamber: Drain Saver:	17 gallons 0.75 hp 1.5" diameter 68"/70 cfm 1.25 gallons 30 cubic inches	17 gallons 0.75 hp 1.5" diameter 68"/70 cfm 1.25 gallons 30 cubic inches		
General Cleaning Width:	17-FB: 17" 20-FB: 20" 23-FB: 23"	17-FD: 17" 20-FD: 20" 23-FD: 23" 26-FD: 26" 28-FD: 28" 24-FC: 24"		
Cleaning Rate/Hour (Sq. Ft/Hr): Sound Level:	-	Up to 25,543 's Position for all units		
Optional Equipment				

Optional Equipment

- Spray Hose
- Management "Lockout"
- Key Switch
- Vacuum Wand Attach.
- Onboard Soap
- Variety of Brushes/Pads
- HD Batteries
- W Onboard Soap

• Chemical Free Scrubbing/Stripping