


Power Cleaning Equipment

A COMPLETE FAMILY OF INDUSTRIAL CLEANING EQUIPMENT




First

in

EQUIPMENT LEASING, LLC







KEY FEATURES




Machine Control Panel uses off-the-shelf toggle and marine duty switches and features universal icons which simplifies training.



Vacuum Muffler allows machine to consistently achieve as low as 62 dB for noise sensitive applications while thoroughly drying the floor.



Squeegee Adjustments made simple with quick change squeegee latch allows toolless maintenance and 4-sided squeegee blade.



Front Fill System features a retractable hose for easy filling on standard sink-faucets.



High Performance motors and down pressure provides an unmatched standard of cleaning.



INDUSTRIES

Fabrication Shops

Warehouses

Machine Shops

Automotive Shops


Aviation

Food Packaging

Beverage Distribution

Sports Arenas






EASE OF MAINTENANCE


- 1 Tip Back "Clam Shell" Design
- Access to Batteries
- 3 Access to Scrub Motors
- 4 Access to Solution Filter
- 5 White Vacuum Filter Access
- 6 Full Recovery Tank Access

VIEW INSIDE



TWO SCRUB SYSTEMS TO CHOOSE FROM

DISK



- Brush / Pad Selection
- Lowest Maintenance Cost
- **Gimballed Drivers Improves** Cleaning On Irregular Floors
- Brushes Individually Driven For Unmatched Performance

- Eliminates Dust Mopping
- Scrub & Sweep Simultaneously
- Superior Grouted Tile Cleaning

A DEMONSTRAT FOR

Your Total and Complete **Cleaning Solution Resource** Since 1967

Bortek has over 50 years' experience in the Power Cleaning Equipment and Commercial Supply Industry. We've maintained the best employees, amazing customers, world-class customer service, awesome power cleaning equipment, best-in-the-biz liquid cleaners, and an extensive selection of commercial supplies.

We get a real kick out of helping our customers with their cleaning equipment and commercial supply needs. We love what we do and we're pumped to work with you. Running and managing aspects of a business can be a total headache in and of itself. Maintaining your facility or being responsible for road maintenance/clean-up, just adds to that pressure behind your eyeballs. It's a raw deal sometimes, we understand. That's part of why we do what we do. We like things to be simple.

NTACT 800.6.Bortek 717.737.7591 info@sweeperland.com sweeperland.com **CUSTOMER**

2	김 씨를 싸를 싸를 배를 배를 배를 배를 배로 배로	비통비통비통비통비통비통비통비통비통비통비통
	BODY CONSTRUCTION / DIMENSIONS	
	Tank Material:	Poly 3/8" (10 mm)
	Chassis Construction :	3/16" Steel (5 mm) Powder Coated Steel
	Front Wheels (Diameter × Width) :	$(2\times)$ 12" × 2.75" ([2×] 31 × 7 cm) - Solid Black
	Rear Casters (Diameter × Width) :	$(2\times) 5'' \times 2''$ ([2×] 13×5 cm) - Non-Marking Grey
	Size $(L \times W \times H)$:	$55" \times 26" \times 40"$ (140 × 66 × 102 cm)
	Weight (w/o Batteries) :	441 - 481 lbs (200 - 218 kg)
	Weight (w/ 315 ah Batteries):	775 - 825 lbs (352 - 374 kg)
	BRUSH / PAD SYSTEM	
	Disk Dimensions:	30" - (2×) 15" Diameter (76 - [2×] 38 cm)
	Includes Jaws with Rollers for Wall Protection	34" - (2×) 17" Diameter (86 - [2×] 43 cm)
	Disk Motor:	(2×) 1.0 hp / 350 rpm ([2×] 746 watts)
	Disk Brush Speed:	350 rpm
	Cylindrical Dimensions: 6" Diameter Brush	29" - (2x) 6" x 27" (74 - [2x] 15 x 69 cm) 33" - (2x) 6" x 31" (84 - [2x] 15 x 79 cm)
	Cylindrical Motor:	(2×) 1.0 hp / 350 rpm ([2×] 746 watts)
	Cylindrical Brush Speed:	750 rpm
	Scrub Pressure Actuator Max:	500 lbs (227 kg)
	Brush Pressure Settings:	(5) with Auto Adjust
	POWER SYSTEM	
	System Voltage:	24 VDC
	Standard Battery:	315 ah WET
	Optional Battery: *Includes Onboard Charger	360 ah WET / 335 ah AGM*
	Run Time: **Run times are based on continuous scrubbing run times.	Up to 5.0 Hours**
	Charger:	120VAC / 60 Hz Input - 24VDC / 30 amp Output
	DRIVE SYSTEM:	
	Power:	0.75hp - All Gear / Sealed (559 watts)
	Forward Speed:	0 - 290 ft/min / 0 - 3.3 mph (0 - 88 m/min / 0 - 5 km/h)
	Scrubbing Speed:	0 - 229 ft/min / 0 - 2.6 mph (0 - 70 m/min / 0 - 4 km/h)
	Reverse Speed:	0 - 202 ft/min / 0 - 2.3 mph (0 - 62 m/min / 0 - 4 km/h)
	SOLUTION / RECOVERY SYSTEMS:	
	Solution Tank Capacity:	30 Gallons (114 liters) - w/ Graduated Site Tube
	XL Tank Option Solution Capacity:	35 Gallons (133 liters) - w/ Graduated Site Tube
	Solution Flow / Filter:	0 - 1.0 GPM / Stainless Inline (0 - 4 LPM)
	Recovery Tank Capacity:	32 Gallons (121 liters) - 1.5" diameter Drain Hose
	XL Tank Option Recovery Capacity:	37 Gallons (140 liters) - 1.5" diameter Drain Hose
	Demisting Chamber:	1.25 Gallons (5 liters)
	Drain Saver:	30 cubic inches (492 cubic cm)
	Vacuum Power:	0.8 hp / 3 Stage (640 watts)
	Vacuum Specs (Water Lift / Airflow):	68" / 72 cfm (173 cm / 2 cm/m)
	Squeegee:	42" Curved w/ 4-sided Rear Blade & Quick Change Optional - 36" Squeegee
	GENERAL:	
	Cleaning Width:	30" & 34" - Disk (76 & 86 cm) 29" & 33" - Cylindrical (64, 74, 84 cm)
	Decibels:	62 dB
	Productivity - Theoretical: ***Productivity is based off of ISSA 2010 Cleaning Times	Up to 31,915 sqft (2,965 sqm) ***
	Productivity - Practical: ***Productivity is based off of ISSA 2010 Cleaning Times	Up to 14,851 sqft (1,380 sqm) ***

& Quick Change Latch