

SAFETY DATA SHEET

Date Issued : 06/26/2018

SDS No : Bortek_Ranger

Ranger Oven & Grill Cleaner

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Ranger Oven & Grill Cleaner

GENERAL USE: Remove carbon, grease, and oils from ovens, grills, fryers and vents.

PRODUCT DESCRIPTION: Oven & Grill Cleaner

CHEMICAL FAMILY: Alkali/detergent blend

DISTRIBUTOR

Bortek Industries, Inc.

4713 Gettysburg Road

Mechanicsburg, PA 17055

Customer Service: 7177377162

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEM-TEL (Medical and Transportation): 800-255-3924

POISON CONTROL CENTER (Medical): 800-222-1222

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Corrosion, Category 1B

Eye Corrosion, Category 1

Acute Toxicity (Oral), Category 4

Physical:

Corrosive to Metals, Category 1

GHS LABEL



Corrosion



Exclamation
mark

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H318: Causes serious eye damage.

H314: Causes severe skin burns and eye damage.

H302: Harmful if swallowed.

H290: May be corrosive to metals.

PRECAUTIONARY STATEMENT(S)

Prevention:

P260: Do not breathe fumes, gas, mist, vapors or spray.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P270: Do not eat, drink or smoke when using this product.

P234: Keep only in original packaging.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor/physician.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P363: Wash contaminated clothing before reuse.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P311: Call a POISON CENTER or doctor/physician.

P390: Absorb spillage to prevent material damage.

Storage:

P405: Store locked up.

P406: Store in a corrosion resistant plastic container or a metal container with a resistant inner liner.

Disposal:

P501: Dispose of contents/container according to all local, state and Federal regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Pink Liquid

IMMEDIATE CONCERNS: Causes irreversible eye damage and skin burns.

POTENTIAL HEALTH EFFECTS

EYES: Corrosive, contact causes severe eye burns.

SKIN: Contact causes severe skin irritation and possible burns.

SKIN ABSORPTION: None Expected.

INGESTION: Harmful if swallowed.

INHALATION: Mist is irritating to nose, throat and lungs.

REPRODUCTIVE TOXICITY

TERATOGENIC EFFECTS: None known.

CARCINOGENICITY: Not Established

MUTAGENICITY: None known.

ROUTES OF ENTRY: Eye, skin, ingestion.

CANCER STATEMENT: None

WARNING CAUTION LABELS: Corrosive

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Sodium Silicate	0 - 5	6834-92-0
Sodium Hydroxide	0 - 5	1310-73-2
Potassium Hydroxide	5 - 10	1310-58-3
Polyethylene glycol (octylphenyl) ether Phosphate	0 - 5	52623-95-7
Ethylene glycol butyl ether	0 - 5	111-76-2
Dye	< 0.1	N/A
Water	80 - 90	7732-18-5

4. FIRST AID MEASURES

EYES: Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Seek medical attention immediately.

SKIN: Remove contaminated clothing. Immediately flush with water followed by washing with mild soap. Seek medical attention.

INGESTION: Get immediate medical attention. Do not induce vomiting unless instructed to do so by poison center or physician.

INHALATION: Remove victim to fresh air and monitor. Seek medical advise if irritation persists.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Severe burning sensation, damage marked by burns.

SKIN: Burning sensation, redness, swelling and possible blistering.

INGESTION: Irritation of mouth, throat, along with stomach upset, vomiting.

INHALATION: Irritation of nose, throat and lungs with coughing, sneezing, possible difficulty breathing.

ACUTE EFFECTS: Corrosive to eyes and skin. Harmful if inhaled. Harmful if swallowed

NOTES TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: None

EXTINGUISHING MEDIA: Use an extinguishing agent suitable for the surrounding fire.

EXPLOSION HAZARDS: Fire exposed containers may burst due to increased pressure from heat.

FIRE FIGHTING PROCEDURES: Keep fire exposed containers cool with water stream or mist.

FIRE FIGHTING EQUIPMENT: Not Established

HAZARDOUS DECOMPOSITION PRODUCTS: Not Established

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

LARGE SPILL: Avoid walking in material. Prevent product from entering into stream, soil, storm sewer or other bodies of water.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid discharges into open waterways.

LAND SPILL: Avoid discharge to soil.

AIR SPILL: NA = Not Applicable

GENERAL PROCEDURES: Isolate spill or leak area immediately. Keep unauthorized personnel away. Do not touch or walk through spilled material. Prevent entry into waterways, sewers, or confined areas. Absorb with dry earth, sand or other non-combustible material and transfer to containers.

SPECIAL PROTECTIVE EQUIPMENT: Eye protection, rubber gloves, rubber boots to protect feet.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Close container after use.

HANDLING: Avoid contact with skin and eyes. Wash hands before eating, drinking, smoking or using toilet facilities.

STORAGE: Store in closed container in an area inaccessible to children.

STORAGE TEMPERATURE: Store at ambient temperatures.

STORAGE PRESSURE: Store at ambient atmospheric pressure.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	EXPOSURE LIMITS			mg/m ³
	Type		ppm	
Sodium Hydroxide	OSHA PEL	TWA		2 mg/m ³
	ACGIH TLV	TWA		2 mg/m ³
Potassium Hydroxide	OSHA PEL	TWA		2 mg/m ³
	ACGIH TLV	STEL		2 mg/m ³
Ethylene glycol butyl ether	OSHA PEL	TWA	50	240
	ACGIH TLV	TWA	20	97
	Supplier OEL	TWA	NL	NL
		STEL	NL	NL

ENGINEERING CONTROLS: Provide mechanical ventilation when used in confined areas, or areas with poor ventilation.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Chemical splash goggles and full face-shield.

SKIN: Rubber or other chemical resistant gloves.

RESPIRATORY: Where danger of mist contact may occur, wear NIOSH approved respiratory protection for mists.

PROTECTIVE CLOTHING: Chemical resistant outerwear (tyvek) if contact with spray or mist is anticipated.

WORK HYGIENIC PRACTICES: Wash with soap and water after handling. Do not eat, drink or smoke while using product.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Characteristic.

ODOR THRESHOLD: Not Established

COLOR: Pink

pH: 13.0 to 14.0

PERCENT VOLATILE: >80

FLASH POINT AND METHOD: None

FLAMMABLE LIMITS: N/A

AUTOIGNITION TEMPERATURE: NA = Not Applicable

VAPOR PRESSURE: ~ 20 mm Hg at (68°F)

VAPOR DENSITY: ~ 1 Air = 1

BOILING POINT: 212° F; 100° C

FREEZING POINT: 32° F; 0° C

THERMAL DECOMPOSITION: Not Available

SOLUBILITY IN WATER: Complete

EVAPORATION RATE: (Water =1) 1.0

DENSITY: 9.07

SPECIFIC GRAVITY: ~ 1.087 grams/ml.

VISCOSITY: Water thin.

(VOC): 1.29 % by weight

10. STABILITY AND REACTIVITY

REACTIVITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Reacts violently with strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

INCOMPATIBLE MATERIALS: Strong acids, oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Sodium Silicate	1500 to 3200 mg/kg (rat)		
Sodium Hydroxide	300 to 500 mg/kg (rat)	> 2000 mg/kg (rabbit)	
Potassium Hydroxide	273 mg/kg (rat)	N/A	
Ethylene glycol butyl ether	1300 mg/kg (rat)	> 2000 mg/kg (rabbit)	> 3.1 mg/l

DERMAL LD₅₀: Not Established

ORAL LD₅₀: Not Established

INHALATION LC₅₀: Not Established

SKIN CORROSION/IRRITATION: Corrosive

SERIOUS EYE DAMAGE/IRRITATION: Irritant

GERM CELL MUTAGENICITY: No known significant effects or critical hazards.

CARCINOGENICITY

Chemical Name	NTP Status	IARC Status	OSHA Status
Ethylene glycol butyl ether	No listed substance	Group 3 - Not classifiable as to its carcinogenicity to Humans	No listed substance

IARC:

The International Agency for Research on Cancer (IARC) has concluded that there is inadequate evidence for carcinogenicity of 2-butoxyethanol in humans, but limited evidence in experimental animals (Group 3 - not classifiable as to its carcinogenicity to humans).

REPRODUCTIVE TOXICITY: No known significant effects or critical hazards.

STOT-SINGLE EXPOSURE: No known significant effects or critical hazards.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Not Established

ECOTOXICOLOGICAL INFORMATION: This material may be toxic to aquatic life.

AQUATIC TOXICITY (ACUTE): Not Established

CHEMICAL FATE INFORMATION: Not Established

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. If discarded, this material and its containers should be treated as hazardous waste based on the characteristics of corrosivity as defined under federal RCRA regulations (40 CFR 261). Consult local authorities for disposal into public sewer.

FOR LARGE SPILLS: Consult with local and state authorities for large volume disposal.

PRODUCT DISPOSAL: Any method in accordance with local, state, and federal laws. Best method is to recycle or reuse for intended purpose.

EMPTY CONTAINER: Rinse container with clear water. Offer container for recycling, or dispose of in trash.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Compound, Cleaning Liquid

TECHNICAL NAME: Potassium Hydroxide Solution

PRIMARY HAZARD CLASS/DIVISION: 8

UN/NA NUMBER: 1760

PACKING GROUP: III

PLACARDS: Corrosive

LABEL: Certain package sizes determine the proper labeling of containers. Consult manufacturer for specific information

regarding proper labeling.

OTHER SHIPPING INFORMATION: Certain shipping modes and packaging sizes may have exceptions from the transport regulations. The classifications/information provided above may not reflect applicable exceptions. Contact the manufacturer for more specific information on the proper shipping of this material.

U.S. CUSTOMS HARMONIZATION NUMBER: 3402.90.10.00

AIR (ICAO/IATA)

SHIPPING NAME: Contact manufacturer for more information.

VESSEL (IMO/IMDG)

SHIPPING NAME: Contact manufacturer for more information.

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Corrosive



Limited
Quantity
Ground

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Health - Acute

313 REPORTABLE INGREDIENTS: 2-butoxyethanol 111-76-2 (Category: N230 Certain Glycol Ethers)

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Ethylene glycol butyl ether	0 - 5	111-76-2

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: No listed substance

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Not Established

Chemical Name	Wt.%	CERCLA RQ
Sodium Hydroxide	0 - 5	1,000 lbs.
Potassium Hydroxide	5 - 10	1,000

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All ingredients are listed on the TSCA Chemical Inventory.

STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
Sodium Silicate	Pennsylvania Right to Know Substance New Jersey Right To Know Substance
Sodium Hydroxide	Massachusetts Right to Know Substance New Jersey Right To Know Substance Pennsylvania Right to Know Substance Rhode Island Right to Know Substance
Potassium Hydroxide	Massachusetts Right to Know Substance Pennsylvania Right to Know Substance New Jersey Right To Know Substance Rhode Island Right to Know Substance
Ethylene glycol butyl ether	Massachusetts Right to Know Substance Pennsylvania Right to Know Substance New Jersey Right To Know Substance

CALIFORNIA PROPOSITION 65: None

CARCINOGEN:

The International Agency for Research on Cancer (IARC) has concluded that there is inadequate evidence for carcinogenicity of

2-butoxyethanol in humans, but limited evidence in experimental animals (Group 3 - not classifiable as to its carcinogenicity to humans).


16. OTHER INFORMATION

Date Prepared: 06/26/2018

HMIS RATING

HEALTH	<input type="checkbox"/>	3
FLAMMABILITY		0
PHYSICAL HAZARD		0
PERSONAL PROTECTION		D

NFPA CODES



MANUFACTURER DISCLAIMER: This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of the product either alone or in combination with other products. It is the responsibility of the employer and/or user to provide a safe workplace, using health and safety information contained herein as a guide. This company will accept no liability for damages or losses incurred from the improper handling and use of this product.