Bortek
INDUSTRIES, INC.

HOT SHOT
Floor Stripper

MADE IN THE USA

YOUR CLEANING SOLUTIONS RESOURCE®

DESCRIPTION

HOT SHOT is a heavy duty, no-rinse, speed floor stripper. It's also one of the most effective floor finish emulsifiers ever developed. It dissolves multiple layers of aged and built-up finishes almost instantly. HOT SHOT may be used as a no-scrub floor stripper or with the conventional floor machine and pad, depending on the concentration of the product and the condition of the floor. HOT SHOT dissolves even the toughest of straight acrylic sealers with ease. Effortlessly vacuumed up after the stripping process is completed, HOT SHOT is designed for floor care professionals whose time is at a premium. HOT SHOT is unmatched when it comes to its effectiveness and value.

FEATURES

- Heavy Duty Formula
- No-rinse

BENEFITS

- Tough jobs made easy
- Low end-use cost
- Fast acting

AREAS OF USE

- Vinyl
- Vinyl Asbestos Flooring
- Concrete Flooring
- Linoleum Flooring
- Rubber Tile Flooring*
- Tile Flooring
- Ceramic Tile Flooring
- Flagstone Flooring
- Asphalt Tile Flooring*
- Terrazzo Flooring

*NOTE: Asphalt Tile and Rubber Flooring could be affected by stripping solutions in high concentrations. Always test a small, out-of-sight section of the floor before proceeding.

DIRECTIONS

The desired concentration will depend on the build-up and age of the polish film. As a starting point, dilute with cold water as follows:
For average build-ups: Dilute 1 to 3 with cold water.
For moderate build-ups: 1 to 2 with cold water.
For heavy, aged build-ups: 1 to 1 with cold water.
For use with a floor machine: Dilute 1 to 8-16 parts cold water.

Apply a generous solution onto the floor that's to be stripped. Allow the solution to stand for about 5 minutes, keeping the floor wet at all times. If mop stripping, agitate with the mop. If using a Bortek automatic floor scrubber or rotary floor machine, no mop agitation is required. Pick-up the solution with a Bortek wet-vacuum, automatic scrubber or hand tool / wet mop. Allow floor to dry thoroughly prior to applying any sealer or finish. If desired, a rinsing step can be added.

AVAILABILITY

Packaging	Item #
Case of Four 1-Gallon Bottles	86-4
Case of Two 2.5 Gallon Bottles	86-5
55 Gallon Tote	86-55
275 Gallon Tote	86-275

More GHS information can be found on this product's label.

Health-3 Flammability-0 Reactivity-0
HMIS RATING

Order Online & Manage Your Account 24/7 with **CUSTOMER LINK**
800.626.7835

EQUIPMENT ● PARTS ● RENTALS ● SERVICE ● SUPPLIES

Corporate Headquarters
4713 Gettysburg Road
Mechanicsburg, PA 17055