

DESCRIPTION

Permacote 180 is a metal cross-linked, acrylic floor finish with high initial gloss and durability. Excellent for schools and institutions. A true workhorse in any maintenance program. Dries to a hard durable finish that withstands daily high traffic yet responds well to low or high speed spray-buffing. Designed for low or high maintenance floor care programs.



DIRECTIONS

PREPARATION: If stripping is necessary, use a high quality stripper and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely. If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.

FINISHING: Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Four coats is ideal initially, depending on the condition of the floor and desired gloss.

MAINTENANCE: The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.



Order Online & Manage CUSTOMER

🎨 EQUIPMENT 🏶 PARTS 🤌 RENTALS 🧌 SERVICE 🗫 SUPPLIES 🛛

Corporate Headquarters 4713 Gettysburg Road Mechanicsburg, PA 17055