


Bortek
INDUSTRIES, INC.

PERMACOTE 250

High Solids Floor Finish



YOUR CLEANING SOLUTIONS RESOURCE®

DESCRIPTION

Permacote 250 is a premium quality, high solids, metal cross-linked acrylic floor finish designed to give exceptional initial gloss with minimum amount of coats. Dries to a hard durable finish that withstands daily high traffic yet responds well to low or high speed spray-buffing. Designed for low or high maintenance floor care programs.

FEATURES

- Metal Cross-linked
- High Solids
- Flexible maintenance
- "Wet look" gloss

BENEFITS

- Provides extended wear
- Requires less coats
- Responds to any floor care program
- Floors look great

AREAS OF USE

- Classrooms
- Healthcare facilities
- Office buildings
- Hallways
- Entrances
- Hospitals
- Vinyl Tiles
- Linoleum
- Terrazzo
- Slate
- Concrete

DIRECTIONS

PREPARATION: If stripping is necessary, use a high quality stripper and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely. If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.

FINISHING: Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Four coats is ideal initially, depending on the condition of the floor and desired gloss.

MAINTENANCE: The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

AVAILABILITY

Packaging

Case of Four 1-Gallon Bottles
Case of Two 2.5-Gallon Bottles
55 Gallon Drum

Item

133661B
6212008
133663



More GHS information can be found on this product's label.

Health-1 Flammability-0 Reactivity-0

HMIS RATING

FOR THIS PRODUCT'S SDS, VISIT OUR WEBSITE AT WWW.SWEEPERLAND.COM

