



TUFFCOTE CS

Concrete Cure & Seal



YOUR CLEANING SOLUTIONS RESOURCE®

DESCRIPTION

Tuffcote CS is a protective acrylic coating, for curing and sealing new and old concrete surfaces. This water based coating can be used for interior and exterior applications. Protects against grease, dirt, chemicals, and stains. Fast drying with no solvent fumes makes this an ideal product for use in closed areas. Curing membrane performance meets ASTM C-156 requirements.

Manufacturer's Recommendation: This coating is to be applied without thinning.
 VOC Content = 36.3 grams/liter, excluding water

FEATURES

- Versatile
- Chemical resistant
- No solvent fumes

BENEFITS

- For interior or exterior and new or older hard surfaces
- Protects concrete

AREAS OF USE

- New concrete surfaces
- Old concrete surfaces
- Exterior concrete
- Interior concrete
- Concrete
- Terrazzo
- Brick
- Flagstone
- Quarry tile

DIRECTIONS

PREPARATION: If sealing old concrete, remove all grease, oil, and other foreign material by scrubbing with a heavy-duty cleaner and good scrub brushes. Smooth dense concrete surfaces should be acid conditioned before application. Rinse floor thoroughly with clear water and allow floor to dry.

APPLICATION: Spread a liberal coat evenly across the floor using a mop, squeegee, roller, lamb's wool applicator or other appropriate applicator. If higher gloss is desired apply a second coat after allowing first coat to dry for at least 45 minutes. Surface temperature should be above 50°F. Allow final coat to dry at least 12 hours before allowing heavy traffic onto floor.

AVAILABILITY

Packaging

Case of Two 2.5-Gallon Bottles

Item

AQU-5



More GHS information can be found on this product's label.

Health-1 Flammability-0 Reactivity-0

HMIS RATING

FOR THIS PRODUCT'S SDS, VISIT OUR WEBSITE AT WWW.SWEEPERLAND.COM

