



3518-SC Trailer Jetter



The Ultimate Workhorse

With a water tank that doubles the capacity of any smaller trailer unit and a powerful engine/pump combination, this model efficiently tackles a wide range of line cleaning duties all the way up to 24" mains. The rigid chassis and axle design give it stability, so you can haul a full tank of water at highway speeds.

Standard unit color is safety yellow or white - customer choice. Can be custom painted to match almost any color, for an additional charge.

Available Options

- 100' 1/2" Extra Hose on Main Reel (PN OBJ-100-12AH)
- 200' 1/2" Extra Hose on Main Reel (PN OBJ-200-12AH)
- Anti-Freeze System (PN OBJ-234)
- Arrow Board (PN OBJ-144)
- Auto Level Wind Guide Mounted (PN OBJ-9032)
- Cone Holder Only (PN OBJ-137)
- Custom Decals (two)
- 80HP JohnDeere Diesel Engine (PN OBJ-80JDO)
- 85HP Cummins Diesel Engine (PN OBJ-85CO)
- E-Stop Assembly (PN IC-100405-01)
- Foot Control Swinger (PN OBJ-187A)
- Garden Hose Reel 1/2" - 50' (PN OBJ-123000L)
- Garden Hose Reel Electric 100' (PN OBJ-294)
- Garden Hose Reel Manual 100' COX (PN OBJ-293)
- Hydraulic Surge Brakes (PN 35005B)
- IntelACount® (PN OBJ-2430E)
- Low Water Shutdown (PN OBJ-2424)
- Level Wind Guide w/Counter (PN OBJ-2430A)
- Paint Custom (Paint Code Required) (PN PAINT-CUSTOM)
- STD_Paint - Safety Yellow (PN PAINT-1Y)
- STD_Paint - White Enamel (PN PAINT-3W)
- Pintle Hitch (PN OBJ-1081P)
- Pulsator LP301A (PN 22737)
- Recirculation System (PN OBJ-1/2"RECIRC)
- Rotating Beacon-Fixed (PN OBJ-241B)
- Side Panels (two) - Painted (PN OBJ-2523P)
- Spare Tire Holder w/Tire 16" (PN OBJ-9060-700016)
- Tank Shroud Aluminum (PN 3500ADS)
- Tank Shroud Steel (PN 3500SS)
- Wireless Remote (PN OBJ-101)

"Swinger" Reel—190° Pivot

Makes line cleaning a simple job because it allows for:

- Easy access to the manhole regardless of how trailer is parked
- Tethered hand control
- Variable-speed control
- Hydraulic driven
- 'Catwalk' fenders

Standard Components

350 Gallon Polyethylene Tank

Plate mounted with sump and side baffles
Crowned top & side stabilizers for added strength
Sufficient water supply for necessary water flow
12" Manhole with basket

High-Impact Thermoplastic Sewer Hose

Easy to keep clean (retains no bacteria-causing residue).
Maintains stiffness and is abrasion resistant.

Standard 400' of 1/2" hose reaches from manhole to manhole.
Reel capacity is 1,000' of 1/2" hose.

Cummins Diesel Engine 65hp

Murphy safety gauges with auto - shutdown
Variable electronic throttle control

Available Accessories

- Artillery Nozzle Kit (PN 121840AR)
- Cavalry Nozzle Kit (PN 121840CA)
- Cone Safety Red 18" tall (PN OBJ-714)
- Fill Hose 25' (PN J-2439)
- Grit Catcher 6" (PN OB00016A)
- Grit Catcher 8" (PN OB00018A)
- Infantry Nozzle Kit (PN 121840IN)
- Kit -Emergency Hand Crank (PN OBJ-300)
- Manhole Cover Hook (PN 015-438)
- Nozzle Extension - Finned 1/2" (PN J-40-7)
- Nozzle Extension - NonFinned 1/2" (PN J-40-3)
- Root Cutter Kit (PN OBJ-1467)
- Rotating Beacon - Magnetic Mount (PN RL650A)
- Strobe Light - Magnetic Mount (PN SL650A)
- Tiger Tail - 2" x 36" (PN J-2204)
- Tiger Tail - 3" x 36" (PN J-2203)
- Tiger Tail - 3" x 42" (PN J-2205)
- Tire & Rim 16" Spare 8 lug (PN J-700-19)
- Upstream Pulley Guide (PN J-2401)
- Washdown Gun w/Hose (PN 15007-B)
- Work Light - Magnetic Mount (PN OBJ-500R)

18GPM@4,000PSI Pump

- Triplex pump

Single-Axle Trailer

The Trailer Jetter is rated to carry a full tank of water to the job . . .

- 6" channel frame
- A-frame hitch
- 2 - 5/16" ball hitch
- 7,000 lb. DOT-rated axle
- ST-235 x 85R16 tires
- Electric brakes

Other Standard Components

- Two nozzles: penetrator & flusher
- PVC tank drain valve with stainless steel strainer
- Direct driven "live" hydraulic system with 17-gallon tank
- 17-gallon fuel tank with cap-mounted gauge.
- Air purge system
- 20' Leader hose contrasting color
- Two (2) aux 12V power supply outlets
- 2" PVC fill pipe
- Level Wind Guide

Signature: _____ Printed Name: _____ Date: _____