

**AIR 80 WD (2V)** is a powerful wet and dry vacuum for non-electric industrial environments. Compact and durable, it's a practical solution for routine cleaning of dust and liquid spills.

Available with ATEX Z22 or Z1, 2, 21 & 22 certification



## Features

- ✓ Compact and portable
- ✓ 2-unit Venturi system (continuous use / maintenance-free)
- ✓ Low air consumption
- ✓ Interchangeable wet / dry filtration
- ✓ Liquid shut-off valve
- ✓ Powder coated steel construction
- ✓ Large storage capacity
- ✓ Discharge hose

## Filtration

Dry Type	Bag
Dry Material	Nylon + Polyester - Class L
Dry Surface Area	9 ft <sup>2</sup> (1 m <sup>2</sup> )
Wet Type	Bag
Wet Material	Polypropylene - 300 µm
Wet Filter Surface	9 ft <sup>2</sup> (1 m <sup>2</sup> )

## Optionals

- Cart Filter Kits (10-125 µm)
- Immersion Pump
- Stainless Steel Tank
- Earth Grounding
- ATEX Certified Version (Zone 22)
- ATEX Certified Version (Zones 1, 2, 21 & 22)
- Partial or Full Stainless Steel Frame
- More Power Sources Available By Request

## AIR 80 WD (2V)

Air Supply	CFM (L/min)	105.9 (3000)
Air Supply Pressure	PSI (bar)	87 (6)
Air Supply Hose	in (mm)	3/8 (10)
Max Airflow	CFM (m <sup>3</sup> /h)	176.6 (300)
Max Water Lift	inH <sub>2</sub> O (mmH <sub>2</sub> O)	164.6 (4180)
Capacity	gal (L)	21 (80)
Dimensions	in (WxLxH)	21 x 23 x 39
Weight	lbs (kg)	73 (33)
Noise Level (EN ISO 3744)	dB(A)	73
Suction Inlet	in (mm)	3 (80)