




AIREX 45 (2V) is a versatile air-operated vacuum that can solve dust problems in almost any light industry. It's a practical and safe solution for ATEX zones 1, 2, 21 and 22.

ATEX CERTIFIED FOR ZONES 1, 2, 21 & 22 / 2GD

EX II 2D Ex h IIB C T 85° C Db
EX II 2G Ex h IIB T6 Gb



652 COMPLIANT

Features

- ✓ Compact, portable and constructed with steel
- ✓ 2-unit Venturi system (continuous use / maintenance-free)
- ✓ Low air consumption
- ✓ Bonding and grounding
- ✓ Removable stainless steel collection tank
- ✓ Accessory basket
- ✓ Versatile and lightweight
- ✓ Integrated cleaning system
- ✓ **ATEX Certified for Zones 1, 2, 21 & 22 and NFPA 652 compliant**

Filtration

| | |
|------------------------------|--|
| Primary Filter | Star |
| Surface Area | 22 ft ² (2 m ²) |
| Media Class (IEC 60335-2-69) | Antistatic Polyester - Class M |
| Cleaning System | Manual |

Optionals

- Certified HEPA Class H14 (99.995% @ 0.18 µm)
- Partial or Full Stainless Steel Frame
- More Power Sources Available By Request
- Other Certifications Available By Request

AIREX 45 (2V)

| | | |
|---------------------------|---|--------------|
| Air Supply | CFM (L/min) | 105.9 (3000) |
| Air Supply Pressure | PSI (bar) | 87 (6) |
| Air Supply Hose | in (mm) | 3/8 (10) |
| Max Airflow | CFM (m ³ /h) | 176.6 (300) |
| Max Water Lift | inH ₂ O (mmH ₂ O) | 164.6 (4180) |
| Capacity | gal (L) | 12 (45) |
| Dimensions | in (WxLxH) | 28 x 22 x 50 |
| Weight | lbs (kg) | 108 (49) |
| Noise Level (EN ISO 3744) | dB(A) | 73 |
| Suction Inlet | in (mm) | 3 (80) |

COPYRIGHT © 2019 DELFIN INDUSTRIAL CORPORATION. ALL RIGHTS RESERVED.