



AIREX 80 W (2V) 1-2G is a pneumatic wet vacuum designed for use in potentially explosive environments. Its steel body and motor head provide high resistance in industrial environments.

ATEX CERTIFIED FOR ZONES 1, 2, 21 & 22 / 2GD

EX II 1/2G Ex h IIB T6 Ga/Gb



652 COMPLIANT

Features

- ✓ Compact, portable and constructed with steel
- ✓ 2-unit Venturi system (continuous use / maintenance-free)
- ✓ Low air consumption
- ✓ Bonding and grounding
- ✓ Discharge hose
- ✓ Liquid shut-off valve
- ✓ **ATEX Certified for Zones 1, 2, 21 & 22 and NFPA 652 compliant**

Filtration

Primary Filter	Cartridge
Dry Material	Antistatic Polyester - Class M
Primary Surface Area	.3-11.4 ft ² (1.6-290 m ²)
Secondary Filter	Activated Carbon

Optionals

- Partial or Full Stainless Steel Frame
- Carbon Activated Filter
- More Power Sources Available By Request
- Other Certifications Available By Request

AIREX 80 WD 2V

Air Supply	CFM (L/min)	106 (3000)
Air Supply Pressure	PSI (bar)	87 (6)
Air Supply Hose	in (mm)	3/8 (10)
Max Airflow	CFM (m ³ /h)	176.6 (300)
Max Water Lift	inH ₂ O (mmH ₂ O)	164.6 (4180)
Capacity	gal (L)	21 (80)
Dimensions	in (WxLxH)	24 x 21 x 43
Weight	lbs (kg)	79 (36)
Noise Level (EN ISO 3744)	dB(A)	73
Suction Inlet	in (mm)	3 (80)