

DG 50 SE is one of Delfin's most versatile three-phase vacuums. Despite being so compact, it features a 2-stage side channel blower for moving heavier materials.

Available with Limited NRTL or ATEX Z22 certification



Optionals

- Certified HEPA Class H14 (99.995% @ 0.18 μm)
- PTFE Coated Filter (Class M)
- NOMEX Heat Resistant Filter
- Oil Mists Filter Kit
- Liquid shut-off valve
- Cyclone Filter Protector

DELFIN INDUSTRIAL CORPORATION

Features

- ✓ Compact, portable and constructed with powder coated steel
- ✓ 2-stage side channel blower (continuous use / no maintenance up to 30,000 hours)
- ✓ Pressure relief valve
- ✓ Large filter surface
- ✓ Removable collection tank with two-handed safety release
- ✓ Performance indicator light
- ✓ Integrated cleaning system
- ✓ Very customizable

Filtration

| Primary Filter | Star | |
|------------------------------|--|--|
| Surface Area | 32 ft ² (3 m ²) | |
| Media Class (IEC 60335-2-69) | Antistatic Polyester - Class M | |
| Cleaning System | Manual | |
| Air Load - ft/min (m/h) | 6.9 (127) | |

- Steel Ring For Polyliner Bags
- Sieve Grid and Discharge Valve
- Partial or Full Stainless Steel Frame
- Pressure Differential Kit

877-205-9015 •

- Ring Bolt and Fork Lift Intakes
- ATEX Certified Version (Zone 22)
- Limited NRTL Certification (Class II, Div. 2)
- Other Cleaning Systems Available
- More Power Sources Available By Request

DG 50 SE

COPYRIGHT © 2019 DELFIN INDUSTRIAL CORPORATION. ALL RIGHTS RESERVED

| Voltage | V - Hz | 230/460 - 60 / 3~ |
|---------------------------|-------------------------|-------------------|
| Power | HP (kW) | 6.4 (4.8) |
| Max Water Lift | inH2O (mmH2O) | 137.8 (3500) |
| Max Airflow | CFM (m ³ /h) | 223.7 (380) |
| Electrical Protection | IP Class | 55 |
| Capacity | gal (L) | 26 (100) |
| Dimensions | in (WxLxH) | 26 x 46 x 57 |
| Weight | lbs (kg) | 320 (145) |
| Noise Level (EN ISO 3744) | dB(A) | 73 |
| Suction Inlet | in (mm) | 3 (80) |